


coupleurs de sécurité conformes à la norme ISO 4414 série SN 20 profil ISO 6150 B-12 - US MIL 4109




Orientable

Débit:
780 NI/min
à 6 bar ($\Delta P : 1 \text{ bar}$)


Pression:
0 - 16 BAR








SN 21 **coupleur mâle BSP cylindrique avec joint monté**



CODE	A	B	D	L	CH	DN
SN21 644	1/4	6,5	25	69,5	21	5,5
SN21 633	3/8	7	25	69,5	21	5,5
SN21 622	1/2	8,5	25	72	25	5,5

SN 22


coupleur femelle BSP cylindrique



CODE	A	B	D	L	CH	DN
SN22 644	1/4	9	25	73	21	5,5
SN22 633	3/8	10	25	75	21	5,5
SN22 622	1/2	11	25	77	24	5,5

SN 25


coupleur avec douille cannelée



CODE	Ø Tube	A	D	L	CH	DN
SN25 606	6	7	25	88	21	5,5
SN25 608	8	9	25	88	21	5,5
SN25 610	10	11	25	88	21	5,5

SN 321



distributeur à 2 voies, implantation mâle BSP conique



CODE	A	H	L	CH	DN
SN321 44	1/4	96	149	17	5,5
SN321 33	3/8	100	155	20	5,5
SN321 22	1/2	98	141	25	5,5



SN 322

distributeur à 2 voies, implantation femelle BSP cylindrique




CODE	A	H	L	CH	DN
SN322 44	1/4	80	131	17	5,5
SN322 33	3/8	83	131	20	5,5
SN322 22	1/2	103	149	25	5,5


embouts en laiton nickelé - profil US-MIL

221
embout mâle cylindrique


CODE	A	B	L	CH
221 644	1/4	8	36,5	17
221 633	3/8	9	37,5	19
221 622	1/2	10	39	24


222
embout femelle cylindrique


CODE	A	B	L	CH
222 644	1/4	11	36,5	16
222 633	3/8	11,5	37	19
222 622	1/2	14	40	24


225
embout avec douille cannelée


CODE	A	D	L
225 606	6	12	43,5
225 608	8	12	43,5
225 610	10	14	46
225 612	12	16	46


embouts en acier zingué - profil US-MIL

AT 0239
embout mâle conique



CODE	A	B	L	CH
AT 023 901	1/4	9	38	14
AT 023 902	3/8	11	41	17

227
embout mâle cylindrique



CODE	A	B	L	CH
227 604	1/4	8	36,5	17
227 603	3/8	9	37,5	19
227 602	1/2	10	39	24

229
embout femelle cylindrique


CODE	A	B	L	CH
229 604	1/4	11	36,5	17
229 603	3/8	11,5	37	19
229 602	1/2	14	39,5	24

226
embout avec douille cannelée pour tube semi-rigide


CODE	A	D	L
226 606	6	12	43,5
226 608	8	12	43,5
226 610	10	14	46
226 612	12	16	46

AT 0240
embout annelé pour tuyau souple


CODE	A	D	L
AT 024 001	6	12	48
AT 024 002	8	12	48
AT 024 003	10	12	48